

Microphones

KB-500WL

740-820MHZ WIRELESS MICROPHONE SYSTEM

- High carrier frequency for superior reception
- Includes receiver and two microphones, clip and handheld optional
- Dual-channel, user-selectable frequency
- 100 meters service range



SPECIFICATIONS	KB-500WL
Frequency Response	50 Hz-18 kHz $\pm$ 3dB
Dynamic Range	>110dB
Distortion S/N	<0.5%
Ratio Service	>102dB
Range	100 meters
Operating Temperature	5 to 45 degrees C
Carrier Frequency Range	740~820 MHz
MICROPHONE:	
Frequency Stable Range	0.005%
Carrier Output Power	<30 mW
Pre-Emphasis	75us
RFI Suppression	>40dB
Radio Frequency Type	UHF
Frequency Range	50 kHz
Microphone Type	Dynamic
Power Requirements	3V battery
De-Emphasis	75us
Power Consumption	45 mA
Dimensions	420(L)*220(W)*44(H)
Weight	235 g
RECEIVER:	
Sensitivity	2 micro V
Output Impedance	600 ohms
Output Level	0~800 mV
Power Requirements	DC 16 V
Power Consumption	5 W
Weight	3.5 kg

MC-Z20

2-TONE CHIME MICROPHONE

- Built-in 2-tone chime
- Red LED indicator
- Push to talk switch
- XLR connector



REAR

SPECIFICATIONS	MC-Z20
Frequency Response	40 Hz-16 kHz
Sensitivity	-43dB $\pm$ 2dB
Impedance	200 ohms
Controls	ON/OFF switch
Cable	10 meters
Power Requirements	12V DC
Dimensions	43 x 20 x 7.5 cm
Net Weight	1.05 kg

MC-Z50

DESKTOP MICROPHONE

- High sensitivity, excellent frequency response
- Attractive black ABS base
- ON/OFF switch
- XLR connector



REAR

SPECIFICATIONS	MC-Z50
Frequency Response	50 Hz-15 kHz
Sensitivity	-45dB $\pm$ 2dB
Impedance	600 ohms
Controls	ON/OFF switch
Cable	10 meters
Power Requirements	1.5V DC
Dimensions	44.5 x 25 x 6.5 cm
Net Weight	1.11 kg