

AXIS P1367 Network Camera

Excellent 5 MP surveillance in all light conditions

The 5 MP resolution at full frame rate ensures great video quality with a high level of details. In bright situations the P-Iris gives an optimal image clarity and in complex lighting, or even in the dark, details will be discovered with the help of Forensic WDR together with Lightfinder. The CS-mount camera gives the flexibility to change lenses for different situations. To save bandwidth and storage Axis Zipstream technology optimizes the video stream while maintaining high video quality. Thanks to enhanced processing capabilities the camera is optimized for adding video analytics applications.

- > **5 MP resolution at 25/30 fps**
- > **CS-mount and i-CS support**
- > **Lightfinder and Forensic WDR**
- > **Zipstream**
- > **Enhanced capabilities for analytics**



AXIS P1367 Network Camera

Camera		Notification: email, HTTP, HTTPS and TCP External output activation Video recording to edge storage, Play audio clip Pre- and post-alarm video buffering PTZ preset, Guard tour, Overlay text Day/Night switching, Status LED activation Send SNMP trap	
Image sensor	1/2.9" progressive scan RGB CMOS		
Lens	IR corrected, CS-mount lens, P-Iris Varifocal 2.8–8.5 mm, F1.2 Horizontal field of view: 104°–36° Vertical field of view: 55°–20°		
Day and night	Automatically removable infrared-cut filter		
Minimum illumination	Color: 0.15 lux B/W: 0.03 lux, at 50 IRE F1.2		
Shutter time	1/55500 s to 2 s	Data streaming	Event data
Video		Built-in installation aids	Focus assistant, pixel counter, remote back focus
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	General	
Resolution	3072x1728 (5 MP) to 160x90	Casing	Metal (zinc) Color lid: White NCS S 1002-B Color chassis: Black NCS S 9002-N
Frame rate	25/30 fps (50/60 Hz) in all resolutions	Mounting	¼"-20 tripod screw thread Camera stand included
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/ABR/MBR H.264	Sustainability	PVC free
Multi-view streaming	Up to 8 individually cropped out view areas	Memory	1 GB RAM, 512 MB Flash
Image settings	Saturation, contrast, brightness, sharpness, Forensic WDR: Up to 120 dB depending on scene, white balance, day/night threshold, exposure mode, exposure zones, compression, orientation: 0°, 90°, 180°, 270° including Corridor Format, mirroring of images, dynamic text and image overlay, privacy masks	Power	8–28 V DC, max 8.8 W, typical 5.0 W Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3, max 8.9 W, typical 5.0 W
Pan/Tilt/Zoom	Digital PTZ Uploadable PTZ driver (Pelco D pre-installed)	Connectors	RJ45 10BASE-T/100BASE-TX PoE I/O: 4-pin 2.5 mm terminal block for two configurable inputs/outputs (12 V DC output, max. load 50 mA) RS485/RS422, 2 pcs, 2 pos, full duplex, terminal block DC input, terminal block, 3.5 mm mic/line in, 3.5 mm line out i-CS connector (compatible with P-Iris and DC-iris) Security lock slot
Audio		Storage	Support for microSD/microSDHC/microSDXC card Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see <i>axis.com</i>
Audio streaming	Two-way, full duplex	Operating conditions	0 °C to 50 °C (32 °F to 122 °F) Humidity 10–85% RH (non-condensing)
Audio compression	AAC LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz, LPCM 48 kHz Configurable bit rate	Storage conditions	–40 °C to 65 °C (–40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Audio input/output	External microphone input or line input, line output, built-in microphone (can be disabled)	Approvals	EMC EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KCC KN32 Class A, KN35 Safety IEC/EN/UL 60950-1, IS 13252 Network NIST SP500-267
Network		Dimensions	213 x 80 x 58 mm (8 3/8 x 3 1/8 x 2 1/4 in)
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X (EAP-TLS) ^a network access control, Digest authentication, user access log, signed firmware Brute force delay protection	Weight	750 g (1.7 lb)
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, SRTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, LLDP	Included accessories	Connector kit, Installation Guide, Windows® decoder 1-user license, stand
System integration		Optional accessories	Axis mounts, Axis lenses, Axis midspans, Axis microphones AXIS T92G20 Outdoor Housing For more accessories, see <i>axis.com</i>
Application Programming Interface	Open API for software integration, including VAPIX® and AXIS Camera Application Platform, specifications at <i>axis.com</i> AXIS Guardian with One-Click Connection AXIS Guardian with One-Click Connection ONVIF® Profile G, ONVIF® Profile S, and ONVIF® Profile T, specification at <i>onvif.org</i>	Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available at <i>axis.com/vms</i>
Analytics	Included AXIS Video Motion Detection, active tampering alarm, audio detection Supported AXIS Digital Autotracking, AXIS Perimeter Defender, AXIS Guard Suite including AXIS Motion Guard, AXIS Fence Guard, and AXIS Loitering Guard Support for AXIS Camera Application Platform enabling installation of third-party applications, see <i>axis.com/acap</i>	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese, Polish
Event triggers	Analytics, edge storage events, external input, audio level, time scheduled	Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see <i>axis.com/warranty</i>
Event actions	File upload: FTP, SFTP, HTTP, HTTPS, network share and email	a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (http://www.openssl.org/), and cryptographic software written by Eric Young (ey@cryptsoft.com).	

Environmental responsibility:
[axis.com/environmental-responsibility](#)

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.openssl.org/>), and cryptographic software written by Eric Young (eyay@cryptsoft.com).

Environmental responsibility:

axis.com/environmental-responsibility