

MCR-R15

Media Converter Rack with Internal Power Supply - 15 slots

Overview

The IFS MCR Series Media Converter Rack offers a low-profile (2.4U) design for efficient, high-density media converter installation in a standard EIA 19" rack. The chassis can accommodate up to 15 media converter modules from the IFS MCR Series family of media converters for Fast or Gigabit Ethernet transmission over optical fiber or coaxial cable.



Details

- Standard EIA 19" design
- Plug-and-Play design
- Hot swappable
- Built-in diagnostic indicators
- Convenient universal 100-240VAC power supply
- Two rear panel power bays for redundant power supply operation
- Built-in protection from over-voltage, over-current and short-circuit faults
- Compatible with MCR range of products

MCR-R15

Media Converter Rack with Internal Power Supply - 15 slots

Technical specifications

General

Category	Media Converter Rack
----------	----------------------

Electrical

Power consumption	88 W
-------------------	------

Physical

Physical dimensions	440 x 180 x 103 mm
Net weight	4.3 kg

Environmental

Operating temperature	0 to +50°C
Reliability	MTBF > 50,000 hrs @ 25°C
Operating Temperature	0° ~ 50° C
Storage Temperature	-10° ~ 70° C
Relative Humidity	0 ~ 90% (non-condensing)

Connectors

AC Line-in	IEC Socket
Back plane DC connector	2.5mm DC receptacle (one per slot)

LED Indicators

Power 1 (Green)	On/AC power OR Off/not powered or power failure
Power 2 (Green)	On/AC power OR Off/not powered or power failure
Fan A (Green)	On/fan functioning OR Off/fan malfunction
Fan B (Green)	On/fan functioning OR Off/fan malfunction

Electrical & Mechanical

Input Power	100~240 VAC, 50-60Hz @ 1.5A
Power Consumption	Unloaded: 10 watts / 34BTUs (with 1 Power Supply) Fully loaded: 88 watts / 301BTUs
Output power (backplane)	+5VDC
Enclosure	Metal
No. of slots	15
Fans	2
Dimensions (W x D x H)	17.3 x 7 x 4 in. (440 x 180 x 103mm) 2.4U height
Weight	9.47 lbs. / 4.30kg

Standards Compliance

Regulatory Compliance	FCC Part 15 Class A; CE; UL 60950-1; EN 60950-1; IEC 60950-1
EMI	EN 55022 CLASS A / EN61000-3-2 / EN61000-3-3
EMS	EN 50130-4 / IEC 61000-4-2 / IEC 61000-4-3 / IEC 61000-4-4 / IEC 61000-4-5 / IEC 61000-4-6 / IEC 61000-4-8

Accessories

MCR-RPS	MCR Chassis Redundant Power Supply - 100-240 VAC (130W)
---------	---



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 5 May 2023 - 9:34