

DM862-0

MCP Blue, Gas Extinguishing Hold, 100 Ohm, English, Dutch & French

General

The DM862-0 is a Type B / Dual action manual call point for surface mount applications. It is specifically designed for use with the FEC403EN gas extinguishing panel, and includes language inserts for English, Dutch & French.

Construction

The rugged aluminum housing, combined with a fade resistant coating guarantees a long lasting high quality product. The revolving door, with an opening angle of 180°, contains an interchangeable break glass. The revolving door also contains a special clip, which features as a failsafe, to prevent the door from being closed while the unit is still triggered.

Dual action

The DM862-0 is defined as a type B /dual action manual call point, due to the fact that two actions are required to trigger the manual call point. First the break glass must be broken, and secondly the button must be pushed.

INTERRUPCIÓN DE EMERGENCIA
Sistema de Extinción de Gas

STOP DE EMERGÊNCIA
Sistema de Extinção

ARRÊT D'URGENCE
Système d'extinction De Gaz



Details

- EN12094-3 approved
- Robust aluminium housing
- Type B / Dual action
- Surface mount

DM862-0

MCP Blue, Gas Extinguishing Hold, 100 Ohm, English, Dutch & French

Technical specifications

Physical

Physical dimensions	125 x 125 x 34 mm (W x H x D)
Net weight	400 g
Colour	Blue
Mounting type	Surface mount

Environmental

Operating temperature	-20 to +60°C
Environment	Indoor
IP rating	IP43

Regulatory

Certification	EN12094-3
---------------	-----------

Series resistor

100 ohm

Housing

Aluminum

Dimensions

125 x 125 x 34 mm

Weight

400g

Color

Blue

Operating Temperature

-20°C to +60°C

IP Rating

IP43



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 4 May 2023 - 17:07