

DM865

MCP Red, Manual Fire Alarm, 100 Ohm

General

The DM865 is a Type B / Dual action manual call point for surface mount applications, with burning house functional marking. It is specifically designed for use with the FEC403EN gas-extinguishing panel, and to complement the DM861, DM862 and DM863 manual call points.

Construction

The rugged aluminum housing, combined with a fade resistant coating guarantees a long lasting high quality product. The revolving door, with an opening angle of 180°, contains an interchangeable break glass. The revolving door also contains a special clip, which features as a failsafe, to prevent the door from being closed while the unit is still triggered.

Dual action

The DM865 is defined as a type B /dual action manual call point, due to the fact that two actions are required to trigger the manual call point. First the break glass must be broken, and secondly the button must be pushed.



Details

- Robust aluminium housing
- Type B / Dual action
- Surface mount

DM865

MCP Red, Manual Fire Alarm, 100 Ohm

Technical specifications

Physical

Physical dimensions	125 x 125 x 34 mm (W x H x D)
Net weight	400 g
Colour	Red

Environmental

Operating temperature	-20 to +60°C
Environment	Indoor
IP rating	IP43

Standards & regulation

Certification	EN54-11
---------------	---------

Series resistor

100 ohm

Housing

Aluminum

Dimensions

125 x 125 x 34 mm

Weight

400g

Color

Red

Operating Temperature

-20°C to +60°C

IP Rating

IP43

