

DMN700-ONTR

Conventional MCP, Flush Mount, Red, Double Pole Free Contact With Glass

General

The DMN700-ONTR is a red manual call point for flush mount applications. It offers double pole, changeover contacts with common, normally open and normally closed connections. It is supplied with a EN54 breakable glass and test key. Surface mount applications require the addition of the DM788 or DMN787.

Installation

Installation time and ultimately cost, are of paramount importance. The MCP range directly reflects this need by providing a unique 'plug and play' concept designed specifically to reduce installation time. All new MCP products utilise a special terminal block, where all initial installation cabling is terminated. This terminal block is then simply connected to the back of the MCP. Simple, but effective, with no re-termination required and no time wasted.

Options

Through new standards and legislation, both break glass and re-settable operating elements may now be used. To provide the greatest 'flex-ability', the new MCP range can be configured as either a break glass or re-settable unit by simply changing from one element to another. No other additional parts or alternative products are required.



Details

- Enhanced aesthetics
- Easy to install (plug and play)
- Surface mount options
- Protection hinged cover with Anti-Tamper facility
- Backward compatible
- Key test facility
- May be used with glass or resettable element
- Easy to replace glass
- High quality micro switch

DMN700-ONTR

Conventional MCP, Flush Mount, Red, Double Pole Free Contact With Glass

Technical specifications

Physical

Net weight	110 g
Colour	Red
Material (body)	PC/ABS

Environmental

Operating temperature	-10 to +55°C
Storage temperature	-10 to +55°C
Relative humidity	0 to 95% noncondensing
Environment	Indoor
IP rating	IP24D

Standards & regulation

Certification	EN54-11
---------------	---------

Cable Termination

0.5 - 2.5 mm ²

Max. contact rating (resistive load)

2A @ 30 VDC

