

FD705RVDS

Reflective Beam Smoke Detector 5 - 50 m

General

The FD705RVDS and FD710RVDS consists of an infrared transmitter and receiver in one single compact housing. The infrared signal is reflected by a prism and analysed for smoke presence. It is particularly designed to be used where point smoke detectors are not applicable due to height or inaccessibility. The unit has C/O relay outputs for alarm and fault and fits as such all types of fire panels. The FD705RVDS has a range of 5-50 m and the FD710RVDS has a range of 50-100 m.

Installer friendly

Wiring is restricted to a minimum as the transmitter and receiver are in the same housing. The detector is very easily aligned by checking the red and green LED's. A course "Prism Find" and then "Alignment Mode" fine-tune ensures optimum operation.

Mechanical alignment is provided by two adjustment thumb wheels on two sides of the detector. Adjustment is achievable in both axis.

The low power consumption of the units allows multiple sets to be powered from a single power supply without compromising the systems autonomy.

Reducing false alarms

Alarm thresholds of 25%, 35% and 50% can be selected to suit the environment. If the received infrared signal reduces to below the selected threshold and is present for approximately 10 seconds, the fire relay is activated. The fire alarm offers both an auto reset mode and a latching mode.

If the infrared beam is obscured rapidly to a level of 90 % or greater for approximately 10 seconds the fault relay is activated. This condition can be entered in a number of ways, for example, an object being placed in the beam path, transmitter failure, loss of the prism, or sudden misalignment of the detector. The detector monitors long term degradation of signal strength caused by component ageing or build up of dirt on optical surfaces. The unit may easily be tested by using the graduated obscuration test card supplied.



Details

- Area coverage up to 1500 m² per unit
- Range from 5 - 50 m and 50 - 100 m
- Up to ceiling heights of 25 m
- 10 to 30 VDC operation
- Low current consumption
- Manual or automatic reset
- 3 selectable alarm thresholds
- Self check and automatic contamination compensation
- Automatic discrimination between fire and fault
- Retro operation through prism
- Vertical or horizontal mount
- Easy wiring and unique alignment
- Microprocessor controlled
- EN54/CPD approved
- VDS approved

FD705RVDS

Reflective Beam Smoke Detector 5 - 50 m

Technical specifications

Electrical

Operating voltage	10.2 to 30 VDC
-------------------	----------------

Detection

Range	5 - 50 m
-------	----------

Physical

Physical dimensions	130 x 210 x 120 mm (W x H x D)
---------------------	--------------------------------

Colour	Grey-black
--------	------------

Environmental

Operating temperature	-10 to +55°C
-----------------------	--------------

Environment	Indoor
-------------	--------

IP rating	IP50
-----------	------

Standards & regulation

Certification	EN54-12
---------------	---------

Lateral detection

7.5 m

Current consumption

Quiescent	< 4 mA
-----------	--------

Alarm	< 15 mA
-------	---------

Optical wave length

880 nm

Construction

Flame retardent ABS

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 9 December 2019 - 18:01

