

VRS121000EBS

100-253VAC Input 12VDC 1A Module Power Supply UK Plug (brick)

Overview

The VRS121000EBS & EES power supplies are designed to supply low voltage power for standalone IFS modules. These power supplies accept universal mains input voltages from 100 – 253Vac, and provide a regulated 12Vdc output with a maximum load of 1A.

Model Features

The VRS121000EBS is provided with a fixed mains cable and a moulded UK style 3 pin mains plug. The VRS121000EBS is provided with a fixed mains cable and a moulded EU style 2 pin mains plug.

Installation Advice

This unit is only suitable for installation as permanently connected equipment. The PSU is NOT SUITABLE for direct external installation, unless fitted within an appropriate IP rated enclosure. The PSU should be installed according to all relevant safety regulations applicable to the application.

This unit must be fed from a mains power source having a separate (approved) disconnect device and fitted with a fuse or other over-current protection device rated at 3A maximum. Ensure that the disconnect device used has appropriate earth fault protection to the applicable standard.

Secure PSU case in position using cable ties or other suitable fastening to prevent movement



Details

- Efficient Switch Mode Operation
- Universal Mains Input Voltage 100 – 253Vac
- Fully Regulated 12Vdc output, 1A
- Overload & Short Circuit Protection
- Class II Double Insulated
- CE compliant (EN60950)

VRS121000EBS

100-253VAC Input 12VDC 1A Module Power Supply UK Plug (brick)

Technical specifications

General

Accessory type	Power Supplies
----------------	----------------

Physical

Input Connection	1 meter mains cable fitted with moulded UK or EU plug
Output Connections	Black & White Stripe - positive, Black - negative
Dimensions	65 x 45 x 26 mm
Weight	0.3 kg
Operating Temperature	0°C to +40°C
Storage Temperature	-20°C to +75°C

Power

Input Power	100 - 253Vac, 50/60Hz, 16W
Output Voltage	12Vdc nominal (11.4 - 12.6Vdc)
Output Current	1A max continuous
Ripple at max current	<120mV pk-pk
Fuse (UK version only)	250V 3A 250mm ceramic
Overload Characteristics	Electronic & Thermal Shutdown (N.B. In the event of an overload shutdown, disconnect from the mains for up to 20 seconds)

Compliance

Low Voltage Compliant
EMC Compliant
WEEE Compliant
RoHS Compliant

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 11 February 2019 - 19:40

