

AI671

Apollo Minidisc Remote Indicator (53832-070)

General

The AI671 remote indicator is a lightweight, compact indicator for use in fire protection systems. It may be used in all installations incorporating 600, 800 and 900 series detectors, including the 630, 650, 860, 930, 950 and 990 series, as well as in intrinsically safe applications using the 670 and 970 series detectors.

Features

The AI671 is only 20 mm high and 80 mm in diameter. It comprises two parts - the base that is installed onto a wall or ceiling, and the lid that is fitted to the base with a bayonet lock. An anti-tamper screw in the lid locks the unit together.

Two pairs of keyholes are provided - one for 50 mm and the other for 60 mm fixing centres.

Installation

The AI671 is polarity sensitive.



Details

- Small and non-intrusive
- Low profile
- Anti-tamper fitting
- Mounting holes for 50 or 60 mm fitting

A1671

Apollo Minidisc Remote Indicator (53832-070)

Technical specifications

Electrical

Operating voltage	5 to 36 VDC
-------------------	-------------

Current consumption	25 mA up to 40°C
---------------------	------------------

Physical

Physical dimensions	80 x 20 mm (Ø x H)
---------------------	--------------------

Environmental

Operating temperature	-10 to +60°C
-----------------------	--------------

Environment	Indoor
-------------	--------

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 14 May 2020 - 11:39

