

AS2364W

2000 Series Loop Powered Sounder, Multi-Tone, Deep Base - (WHITE)

General

The AS2364W is a WHITE bodied, deep base addressable room sounder for fire alarm systems running 2000 series addressable fire protocol. Multiple tone selection and full CPD approval ensure conformance to local regulations.

The sounders operate over a 2-wire 2000 series loop and are loop powered i.e. no external power supply is required. They are compatible with automatic phased-start synchronisation controlled from the fire panel. The AS2364W has a IP65 enclosure.

Installation

Device cabling is done to the base and allows the sounder to be fitted and locked into position afterwards. A separate earth terminal is provided in the base for connecting the screen or functional earth when required.

Efficient and versatile

These sounders can be put into different operating modes depending on local requirements. It provides high sound output at a low current, thus reducing power standby requirements and overall system cost. They are supplied with high/low volume settings as standard, allowing final audio adjustments to be made during installation.

The sounder is tone selectable during installation. 32 tone settings are available.



Details

- Loop powered
- High sound output with low current consumption
- Multiple tone selection
- Suitable for multiple stage evacuation with up to 3 pre-set tones
- Automatic synchronisation
- IP65 rated
- CPD certified

AS2364W

2000 Series Loop Powered Sounder, Multi-Tone, Deep Base - (WHITE)

Technical specifications

Elétrica

Operating voltage	17 to 28 VDC
-------------------	--------------

Sirene

Frequency	400 - 2850 Hz *
-----------	-----------------

Físico

Physical dimensions	100 x 104 mm (Ø x H)
---------------------	----------------------

Net weight	250 g
------------	-------

Ambiental

Operating temperature	-10 to +55°C
-----------------------	--------------

Storage temperature	-10 to +55°C
---------------------	--------------

Relative humidity	5 to 95% noncondensing
-------------------	------------------------

Environment	Indoor
-------------	--------

IP rating	IP65
-----------	------

Regulatory

Certification	EN54-3
---------------	--------

Operating voltage

17-28 VDC

Supply current @ 24 VDC

Switch on surge	< 1.2 mA
-----------------	----------

Quiescent	310 µA
-----------	--------

Activated (Sounder)	5.1 mA
---------------------	--------

Activated (Beacon)	NA
--------------------	----

Sounder

Output @ 90° ± 3 dB(A)	97dBA dBA at 1m *
------------------------	-------------------

Selectable tones	32
------------------	----

Frequency range	400 - 2850 Hz *
-----------------	-----------------

Volume adjustment	8 dB
-------------------	------

Environmental

Operating Temperature	-10°C to +55°C
-----------------------	----------------

Storage temperature	-10°C to +55°C
---------------------	----------------

Relative humidity (non condensing)	5% to 95%
------------------------------------	-----------

IP Rating	IP65
-----------	------

Physical

Body	High Impact Polycarbonate
------	---------------------------

Weight	250 g
--------	-------

Dimensions (dia x h)	100 x 104 mm
----------------------	--------------

Cable size	0.28 mm² to 2.5 mm²
------------	---------------------



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 7 April 2023 - 14:09