

AXIS M3066-V Network Camera

4 MP fixed mini dome with HDMI

AXIS M3066-V features day/night functionality and WDR for sharp video even when there's both dark and light areas in the scene. This ultra-compact camera comes factory-focused, can easily be leveled and directed in any direction, plus offers HDMI support enabling streaming to a public view monitor. It supports intelligent analytics and thanks to the memory card slot, you can optionally record at the edge. Furthermore, Zipstream with support for H.264 and H.265 reduces bandwidth and storage requirements. The camera is made with 52% recycled plastics and is PVC/BFR/CFR free. And, its impact- and dust-resistant casing simply snaps on without visible screws.

- > 4 MP video quality
- > WDR and day/night functionality
- > Zipstream supporting H.264 and H.265
- > HDMI output for streaming to a monitor
- > Environmentally friendly



AXIS M3066-V Network Camera

Camera		Event triggers	Analytics, edge storage events Virtual inputs through API
Image sensor	1/2.5" progressive scan RGB CMOS	Event actions	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share, and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP, and SNMP trap Overlay text
Lens	2.4 mm, F2.1 Horizontal field of view: 131° Vertical field of view: 97° Fixed iris, IR corrected	Data streaming	Event data
Day and night	Automatically removable infrared-cut filter	Built-in installation aids	Pixel counter
Light sensitivity	Color: 0.23 lux at 50 IRE, F2.1 B/W: 0.05 lux at 50 IRE, F2.1	General	
Shutter time	1/32500 s to 1/5 s	Casing	IP42 water- and dust-resistant (to comply with IP42, follow Installation Guide), IK08 impact-resistant, polycarbonate/ABS casing Encapsulated electronics Color: white NCS S 1002-B For repainting instructions, contact your Axis partner.
Camera angle adjustment	Pan: ±175° Tilt: ±80° Rotation: ±175° Can be directed in any direction and see the wall/ceiling	Sustainability	52% recycled plastics, PVC-free, BFR/CFR free
Video		Memory	1 GB RAM, 512 MB Flash
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG	Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 1 Typical 2.5 W, max 3.0 W
Resolution	2304x1728 (4 MP) to 320x240	Connectors	RJ45 10BASE-T/100BASE-TX PoE ^b HDMI Type D ^b Audio and I/O connectivity via optional AXIS T61 Audio and I/O Interfaces with portcast technology
Frame rate	25/30 fps with power line frequency 50/60 Hz	Storage	Support for microSD/microSDHC/microSDXC card and encryption Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/MBR H.264/H.265 HDMI	Operating conditions	0 °C to 45 °C (32 °F to 113 °F) Humidity 10–85% RH (non-condensing)
Multi-view streaming	2 individually cropped out view areas	Storage conditions	–40 °C to 65 °C (–40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Pan/Tilt/Zoom	Digital PTZ	Approvals	EMC ICES-3(A)/NMB-3(A), EN 55024, EN 55035, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, ICES-3(A)/NMB-3(A) Safety IEC/EN/UL 62368-1, IS 13252 Environment EN 60068-2-1, EN 60068-2-2, EN 60068-2-6, EN 60068-2-14, EN 60068-2-27, EN 60068-2-78, IEC/EN 60529 IP42, IEC/EN 62262 Class IK08, RoHS, WEEE Network NIST SP500-267
HDMI output	HDMI 1080p (16:9) @25/30 fps (50/60 Hz) HDMI 720p (16:9) @50/60 fps (50/60 Hz)	Dimensions	Height: 56 mm (2.2 in) ø 101 mm (4.0 in)
Image settings	Compression, color saturation, brightness, sharpness, contrast, white balance, day/night threshold, exposure control (including automatic gain control), WDR up to 115 dB depending on scene, fine tuning of low-light behavior, text and image overlay, privacy masks, mirroring, rotation: 0°, 90°, 180°, 270°, including Corridor Format	Weight	150 g (0.33 lb)
Audio		Included accessories	Installation Guide, Windows® decoder 1-user license
Audio input/output	Two-way audio connectivity via the optional AXIS T61 Audio and I/O Interfaces with portcast technology	Optional accessories	AXIS T94B02D Pendant kit AXIS TM3201 Recessed mount AXIS TM3101 Pendant Wall Mount AXIS T94B01P Conduit back box AXIS T94B02M J-Box/Gang box plate AXIS T6101 Audio and I/O Interface AXIS T6112 Audio and I/O Interface Black casing Smoked dome Axis Mounts AXIS Surveillance microSDXC™ Card For more accessories see axis.com
Network		Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at axis.com/vms
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Supported protocols	IPv4, IPv6, USGv6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, SIP, LLDP, MQTT		
System integration			
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF [®] Profile G, ONVIF [®] Profile S, and ONVIF [®] Profile T, specification at onvif.org Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX.		
Analytics	Included AXIS Video Motion Detection, active tampering alarm Supported Autotracking, AXIS Fence Guard, AXIS Motion Guard, AXIS Loitering Guard, AXIS People Counter, AXIS Queue Monitor, AXIS Occupancy Estimator, AXIS Direction Detector, AXIS Tailgating Detector, AXIS Random Selector Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap		

Warranty

Axis 3-year warranty and AXIS Extended Warranty option, see axis.com/warranty

- a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*

- b. *Make sure that the cable has a slim connector plug*

Environmental responsibility:

axis.com/environmental-responsibility