

ZR485-3

ZR485-3 RADIO CALL POINT COMPLETE WITH BATTERY PACK (RED)

General

The ZR485-3 is a wireless, indoor, manual call point operating on 868 MHz.

Wireless systems

The ZR485-3 provides a manual means of initiating a fire alarm in areas where the installation of hard wiring is not an option. The unit is controlled from the main fire alarm panel via a loop wired radio interface module. This arrangement allows both wireless and hardwired devices to be seamlessly located on the same loop wiring.

The ZR485-3 forms part of an extensive range of wireless fire alarm devices that includes both smoke/heat detection as well as notification devices, sounder/beacons and IO units.

Suitable for use on installations specifying the recommendations of BS 5839 Part 1, the callpoint fully meets the requirements of European Standard EN54 Part 11 and is CPD certified.

System operation

The ZR485-3 is operated either by pressing a resettable element (optional) or by breaking a frangible glass with finger pressure. The glass element has a clear vinyl coating on the front surface to prevent operator injury and to inhibit the release of loose fragments as the glass is broken. Both operating elements are easily interchangeable.

Every wireless device controlled through the RLM interface is assigned its own IDENT address with which the main control panel communicates with it. This provides the same system functionality to wireless as well as traditionally hard-wired devices.

System testing

The ZR485-3 is designed for surface mounting and is supplied complete with matching back box. System testing is carried out by using a special key supplied with the call point. When inserted into a slot in the base of the call point moulding, the device is triggered to operate automatically.

Rated at IP42 the ZR485-3 is constructed of ABS plastic and is intended for indoor applications. A red LED indicator, prominently positioned on the call point front plate, flashes when the unit is operated.



Details

- Fully addressable
- Full wireless device status monitoring
- 2-way radio communication
- 5 year battery life at normal conditions
- Dual battery supply
- Range in excess of 150 metres
- No external aerials
- System test facility via test key
- CPD certified

ZR485-3

ZR485-3 RADIO CALL POINT COMPLETE WITH BATTERY PACK (RED)

Technical specifications

General

Wireless frequency	868 MHz
--------------------	---------

Electrical

Power supply type	Batteries
Operating voltage	3.2 VDC
Output transmitter power	0-14dBm (Variable)
Power supply	6 x AA cell Duracell alkaline batteries

Physical

Physical dimensions	87 mm x 87 mm x 61.5 mm
Net weight	276 g
Colour	Red
Mounting type	Surface mount
Material (body)	Moulded ABS

Environmental

Operating temperature	-10 to +70°C
Relative humidity	10 to 95% noncondensing
Environment	Indoor
IP rating	IP24

Standards & regulation

Certification	EN54-11, EN54-25
Approval	EN54:11/25, ENTSI 300:220

Description

Wireless manual callpoint

Compatibility

All ZP addressable systems via RLM

Monitoring

Continuously self-checking

Indication

Alarm LED (red)

