

LRN-410S

4CH 5MP NVR with PoE Switch



Key Features








- Up to 4CH 5MP
- H.265, H.264, MJPEG codec
- 30Mbps network camera recording
- Plug & play by 4 PoE ports
- Up to 1 SATA (Max. 6TB)
- HDMI local monitor
- P2P service (QR code connect)

FC |  | CE | EAC

Display		
Network camera	Inputs	Max. 4CH
	Resolution	5MP ~ CIF
	Protocols	Wisenet, ONVIF
Decoding	Local Display	HDMI: 1920x1080, 1280x720
	Resolution	5MP(30fps), 3MP(60fps), 2MP(120fps), 720p(240fps), D1 (240fps)
Performance		
Record	Compression	H.265, H.264, MJPEG
	Recording Bandwidth	Max. 30Mbps
	Resolution	5MP ~ CIF
	Mode	Normal, Schedule(Continuous/Event), Event (Pre/Post), Dual track Recording
	Event Trigger	Alarm Input, Video Loss, Camera Event(Alarm, MD, Video Analytics, Defocus)
	Event Action	e-Mail, PTZ Preset, Buzzer, Monitor Out
Search & Play	Playback Bandwidth	Max. 32Mbps(4CH simultaneously)
	User	Max. 4 Users (Local 1, Remote 3)
	Simultaneous playback	Max. 4CH(Local Monitor, Network)
	Fisheye Dewarping	WEB / CMS / Mobile
Storage	Supported HDD	Up to 6TB
	HDD Slot	SATA 1ea(Max. 6TB)
Backup	File backup	BU/Exe(GUI), JPG/AVI(Network)
	Function	Multi channel(Upto 4CH) Play, Date-Time/Title display
Network		
Protocol		IPv4, IPv6, TCP/IP, UDP/IP, RTP (UDP), RTP (TCP), RTSP, NTP, HTTP, DHCP (Server, Client), PPPoE, SMTP, ICMP, IGMP, ARP, DNS, DDNS, uPnP, HTTPS, SNMP, ONVIF (Profile-S), SUNAPI(Server, Client)
DDNS		Wisenet DDNS
Transmission Bandwidth		Max. 20Mbps
Audio	Input/Output	4CH(network)
	Compression	G.711, G.726, AAC(16/48KHz)
	Audio Communication	2-Way
Max Remote Users		Search(3), Live Unicast(10), Multicast(20)
Security		HTTPS(SSL) Login Authentication Digest Login Authentication IP Address Filtering User access log 802.1X Authentication(EAP-TLS, EAP-LEAP) Device Certificate(Hanwha Techwin Root CA)
Viewer Software		SSM, Webviewer, Smart Viewer, Wisenet mobile Support SDK/CGI(SUNAPI) for integration to 3'rd party VMS

Functions		
Camera Setup	Item	IP address, Add profile edit, Bitrate, Compression, GOP, Quality, Camera MD setup, Wisestream, Dynamic GOV/FPS, VA Setup Camera video setup (Simple focus, Brightness/Contrast, Flip/Mirror, IRIS, WDR, D&N, SSNR, Shutter, SSDR, DIS), Fisheye Dewarping Mode, Hallway View Setup, Camera Webpage
PTZ	Control	Via GUI, Webviewer
Smart phone	Support Model	iOS, Android
	Protocol Support	RTP, RTSP, HTTP, HTTPS, CGI(SUNAPI)
	Control	Live(Multi-Profile Support), Playback
	Max. Remote Users	Search(3), Live Unicast(10)
Redundancy	ARB	Support
Easy configuration		P2P(QR code)
Interface		
HDMI		1EA
Ethernet		RJ-45(10/100BASE-T) x 1 RJ-45(PoE+) x 4
USB		2EA(Front 1, Rear 1)
System		
System Control		Mouse, IR remocon, Web
Language		English, French, German, Italian, Spanish, Russian, Turkish, Polish, Dutch, Swedish, Czech, Portuguese, Danish, Rumanian, Serbian, Croatian, Hungarian, Greek, Norwegian, Finnish, Korean, Chinese, Japanese, Thai, Vietnamese
Environmental		
Operating Temperature		0°C to +40°C(32°F to 104°F)
Operating Humidity		20% ~ 85% RH
Electrical		
Power Input		54VDC / 1.20A
Power Consumption		Max. 47W(1HDD, PoE on) Max. 7.4W(1HDD, PoE off)
PoE Budget		Max. 35W
Mechanical		
Color / Material		Black / Metal
Dimension (WxHxD)		W300.0 x H47.1 x D208.4 mm (11.8" x 1.85" x 8.2") (1U)
Weight		0.99Kg (2.18lb)

- The latest product information / specification can be found at hanwha-security.com
- Design and specifications are subject to change without notice.
- Wisenet is the proprietary brand of Hanwha Techwin, formerly known as Samsung Techwin.



3	파생 MODEL2	QRN-420S
2	파생 MODEL1	LRN-410S
1	BASIC MODEL	'19.11.12
No.	MODEL NAME	QRN-410
Unit:mm[inch]		SCALE:1/1
Hanwha Techwin		