

ABT-LA60

Fire Line array loudspeaker Power: 60W, 100V

Overview

ABT-LA fire-alarm loudspeakers mean a new quality among the facilities of the kind. ABT-LA30 and ABT-LA60 units are line-array loudspeaker columns, which means they ensure considerably farther reach than conventional units at simultaneous maintenance of high uniformity of sound level in the area of broadcasting. Being line-array acoustic sources, ABT-LA columns feature a unique high directionality in vertical plane so that the sound they generate will rather go exactly towards the controlled audiospace instead of unwanted areas, such as e.g. ceiling or floor. ABT-LA columns are mostly designed for the rooms with high reverberation time as well as for other places where the quality of speech is reduced due to unfavourable conditions. The ABT-LA design allows easy mechanical and electrical integration of the two columns into a single consistent unit which becomes a loudspeaker with higher power output and farther reach. It makes a better use of the benefits offered by the line-array source. Variable geometry of the column allows generating two sound beams to be randomly sent at various angles to the two different areas. Sound transfer band of the ABT-LA columns has been designed to achieve the highest possible fidelity of speech signal reproduction and to ensure unchallenged parameters of the quality of speech, all as required by the standards applicable to the Voice Evacuation Systems.

Solid aluminium enclosure, steel assembly jigs, and IP 65 guarantee long-term failure-free operations under any conditions, both in outdoor and indoor environments. The columns are entirely dustproof and resistant to the impact of direct water jet.



Details

- Line Array Loudspeakers Columns

ABT-LA60

Fire Line array loudspeaker Power: 60W, 100V

Technical specifications

Electrical

Power consumption	60 W
Line operating voltage	100 V
Output level	79 dB
Frequency	136 - 20000

Physical


Physical dimensions	870 x 80 x 110 mm (H x W x D)
Net weight	4.9 kg
Colour	Silver
Mounting type	Wall bracket
Mounting position	Wall
Housing material	Aluminium

Environmental


Operating temperature	-25°C / 70°C
Environment	Indoor / Outdoor
IP rating	65

Standards & regulation

Standards	EN54-24 BS5839-8 thermal protection 1438-CPR-0574
-----------	---



Connect angle:
-15° ÷ +15°



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 19 February 2021 - 16:28

