

WA-AB_06-100/T-EN54

A/B wall speaker 2 x 6 W, WA-AB_06-100/T-EN5424V

Product overview

The WA-AB 06-100/T-EN54V is designed with two independent speakers and 100 V transformers to enable an economic operation of two separated speaker lines (A/B-lines) for highest security demands. In case of a failure of one speaker line the redundancy of the chassis and the transformers will guarantee unimpaired function. Excellent qualified for the installation in sports facilities and schools. The speaker is also compliant with the British Standard BS 5839, Part 8. The 2 x 6 W powered speaker is equipped with two full-range loudspeakers and two 100 V transformer with 3 power adjustments, each. The high-density, shock-resistant MDF wood housing in white provides a low resonance sound. A sturdy front grille made of steel guarantees enduring stability. For additional reliability, a 2-pin-ceramic block, thermal fuses are provided and the speaker chassis are impregnated against wetness.

The speaker is also secured with the high protection class IP54 against the security risks of environmental influences. Quick and easy mounting with screws.



Details

- Wall-mounted AB (2 lines) speaker 2 x 6 W

WA-AB_06-100/T-EN54

A/B wall speaker 2 x 6 W, WA-AB_06-100/T-EN5424V

Technical specifications

Electrical

Power consumption	2 x 6 W
Output level	85 dB

Physical

Physical dimensions	252 x 194 x 82 mm (W x H x D)
Net weight	2.24 kg
Colour	White (RAL 9010)
Mounting type	Wall mount
Mounting position	Wall

Environmental

Operating temperature	-10 to +55°C
IP rating	IP54

Regulatory

Standards	EN54-24
-----------	---------



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 5 April 2023 - 18:46