

AAE-0100

AlarmLine II Analogue EN LHD Cable w/ PVC Sheath, 100 m

General

The AAE-0100 is an analogue linear heat detection cable in a PVC outer sheath, supplied in 100m lengths. It is suitable for indoor applications where sensor cable is unlikely to be subjected to physical damage or exposed to harsh environmental conditions.

In temperature sensitive environments early detection of an abnormal change is crucial to protect safety of life, critical processes and reduce losses. The AAE analogue range of linear heat detection cable use exceptionally durable linear heat detection technologies which provide extensive and continuous coverage, is easy to install and fully integrate with building management systems. The products offer an enviable set of features bringing enhanced benefits and increased safety to the fire protection industry worldwide.

Fast Response Time

This unique sensor cable and its method of control continuously responds to changes in temperature. The technology offers the facility to programme an early warning pre-alarm as well as the specified alarm temperature. If the temperature surrounding the cable reaches the pre-alarm point, the control unit triggers a warning giving the user time to survey the area at risk. Only when the temperature reaches the specified set alarm point will the control unit trigger full alarm.

The Controller

The optional two stage programmable alarm settings make the system and method of overheat detection incredibly flexible and ideal for use in a variety of different environments and applications. The technology automatically compensates for changes in the ambient temperature to maintain the accuracy of alarm temperature as well as offering up to 500 metres of continuous detection per control unit. The controller is compatible with any conventional or addressable fire alarm panel or other building management system.

Reset and Reuse

Analogue LHD cable is "self-restorable" which means it not always necessary to replace the cable after an incident. Once the alarm has been triggered and depending on the severity of the incident the system can simply be reset with minimum disruption and inconvenience.



Details

- VdS EN54-22:2015/prA1:2007
- Open and short circuit detection reduces the risk of false alarms
- Optional pre-alarm setting allows the user to manage risk more effectively
- Cable based sensing allows detection at the point of risk
- Low installation and maintenance costs reduce total cost of ownership
- Suitable for installation in hazardous areas
- Approved to the latest standards

AAE-0100

AlarmLine II Analogue EN LHD Cable w/ PVC Sheath, 100 m

Technical specifications

Physical

Physical dimensions	Diameter 4.83 mm +/- 0.2 mm (0.190" +/- 0.0075")
Net weight	25.6 g per m
Colour	Red

Environmental

Operating temperature	-40 to +125°C
Relative humidity	0 to 99% ambient temperature -40 to +40°C / 0 to 75% ambient temperature greater than +40°C

Regulatory

Certification	CE, EN54-22, VdS
---------------	------------------



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 5 May 2023 - 9:21