

TVD-6101

TruVision HD-TVI analog dome camera, 720P, 2.7 to 13.5 mm motorized lens, 60 m IR, 12 VDC/24 VAC, IP67

Product overview

The TruVision line includes a comprehensive family of HD-TVI infrared (IR) cameras for stand-alone or integrated installations. Designed for optimal image quality over existing coaxial cable, options are available at up to 8Mpx resolution.

Ideal for improving video quality of existing analog surveillance system installations ranging from convenience stores to retail mall parking lots, the TruVision HD-TVI line has the right cameras for your new or existing project and can help you stay within budget constraints without compromising security needs.

The cameras have true day/night capabilities, providing color images by day and black-and-white images under IR operation in low light applications. TruVision HD-TVI cameras are available with either fixed lens or varifocal lens.

Form factors include dome, traditional bullet and turret cameras . Bullet models offer a familiar form factor that features a pre-installed wall mount with cable management. All models are IP67 rated for outdoor installation and select dome models are available with an IK10 vandal-rated enclosure.

All TruVision HD-TVI cameras are designed to install quickly and easily, right out of the box, so you can be up and running in no time.



Details

- 720p HD resolution
- HD-TVI technology for transmitting HD quality video over existing coax cable
- True day/night functionality and infrared illuminators with Smart IR function for capturing images in various lighting scenarios
- IR range of up to 60 m
- IP67 environmental rating
- True wide dynamic range
- 2.7 to 13.5 mm lens
- Dual power 12 VDC / 24 VAC
- IK10 vandal resistant rating
- Provides OSD control via TruVision up the coax control

TVD-6101

TruVision HD-TVI analog dome camera, 720P, 2.7 to 13.5 mm motorized lens, 60 m IR, 12 VDC/24 VAC, IP67

Technical specifications

Généralités

Technology	HD-TVI analog
Video standard	NTSC, PAL
Image settings	Mirror
Video output	BNC Composite PAL / NTSC, HD-TVI

Caméra

Max. resolution	720p
Sensor scan	Progressive
Sensor type	CMOS
Effective pixels (H x V)	1280 x 720
Shutter time	1/25 s (PAL) or 1/30 s (NTSC) to 1/50,000

Performance d'éclairage

WDR type	True WDR
WDR	130dB
Digital noise reduction	3D DNR
Day/night	True Day/Night
Motorized IR cut filter	Yes
Color sensitivity	0.001 Lux @ (F1.2, AGC ON)
B/W sensitivity	0 Lux with IR
Infrared (IR)	Yes
IR range	60 m

Objectif

Lens type	Varifocal
Focal length	2.7 to 13.5 mm
f-stop	f1.2

Réseau

Integration	CGI, ONVIF, PSIA
-------------	------------------

Électrique

Operating voltage	12 VDC or 24 VAC
Power supply type	12 VDC, 24 VAC
Power consumption	7 W max.

Caractéristiques physiques

Physical dimensions	Ø 145 x 111.3 mm
Net weight	865 g
Colour	Grey (Pantone 428c)
Material	Aluminium
Form Factor	Dome

Environnement

Vandal proof	Yes
Impact rating	IK10
Environment	Indoor / Outdoor
Operating temperature	-40 to 60°C
Relative humidity	90% or less, noncondensing
IP rating	IP67

Regulatory

Compliance	CE, REACH, RoHS, WEEE
------------	-----------------------

Compatible TruVision Recorders/Encoders

TVR12HD
TVR44HD
TVR15HD
TVR45HD
TVR46HD
TVE-110/410/810/1610
TVE-120/420/820/1620

Supported Accessories

TVD-VFM	Flush Mount
TVD-LWB-2 (optional)	Wall Mount (with option weather shield)
TVD-LWB-S)	
TVD-SNB with TVD-CB3	Cup base for use with wall mount arm



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 27 June 2023 - 15:10