

FE250

Door Holder, Floor Mounting, 400N, with Release Button

General

The FE250 is a floor mount door holder, in a Bayblend housing, which offers a 400N holding force and a release button. Cable entry is possible from the back or from the sides, and the release button can be located at the bottom, or one of the sides. The metal mounting bracket offers two mounting options: inside – anti-vandal mode & standard (as shown).

Magnet construction

The magnet is constructed with a pressed coil and anti-remenance pin, giving it a protection of IP54. The protection diodes are integrated into this construction.

Housing

The plastic housing is manufactured from Bayblend and contains 30% PA6 glass fiber, which makes it much stronger than standard ABS. Bayblend offers high heat resistance, high impact and notched impact strength, and high stiffness and dimensional stability.

Installer friendly

- For practical ease of installation, the door holder comes complete with electrical screw terminals.
- The housing is predrilled in a practical, standard format for rapid mounting.
- The door holder is supplied complete with a keeper plate, which offer angular adjustment.
- The release button can be position in three different locations: bottom, left or right
- Cable entry can be done in four different locations: back, top, left or right.
- The door holder can be mounted “inside” of metal bracket – anti-vandal mode, or standard/outside.

Approvals

The FE250 is fully approved according to EN1155.



Details

- Low power - 1.6 W
- 400 N holding force
- Anti-remnant ejector
- Spark suppression diode and reverse polarity protection
- Release button
- EN1155 approved
- Metal mounting bracket
- Keeper plate included

FE250

Door Holder, Floor Mounting, 400N, with Release Button

Technical specifications

General

Holding force N (Newton)	400
--------------------------	-----

Release button	Yes
----------------	-----

Spark suppression diode	Yes
-------------------------	-----

Reverse polarity protection	Yes
-----------------------------	-----

Eléctrico

Power supply type	24 VDC
-------------------	--------

Power consumption	1.6 W
-------------------	-------

Duty cycle	100%
------------	------

Físico

Physical dimensions	128 x 95 x 91 mm (H x W x D)
---------------------	------------------------------

Medioambiental

IP rating	IP54 (magnet)
	IP42 (connection)

Regulatory

Standards	EN1155
-----------	--------



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 9 June 2023 - 8:58