

SPB-2P

Plug-in base, PW

General

The SPB-2P is a polar white, first fix plug in base for the ZP755 series sounders and sounders with visual indicators.

First fix wiring option

The SPB-2 pluggable bases provide a basis for terminating loop wiring at first fix stage. Forming an integral part of the overall unit assembly, the bases are provided with slots for screw fixing, either directly to the building structure, or a wide range of international conduit boxes. Bases feature large wiring terminals with captive clamping washers to ensure secure termination.

Robust manufacture

Bases are manufactured in moulded ABS and are also available in grey, red and white.



Details

- First fix facility
- Ease of installation
- Large wiring terminals

SPB-2P

Plug-in base, PW

Technical specifications

General

Compatibility	ZP755 sounders and sounders with visual indicators
---------------	--

Electrical

Operating voltage	-0 16 to 22 VDC from panel 24 VDC from external supply
-------------------	--

Physical

Physical dimensions	127 x 5 mm (Ø x H)
Net weight	61 g
Colour	Polar white
Mounting type	Surface mount
Material	Moulded ABS

Environmental

Operating temperature	-10 to +75°C
Relative humidity	20 to 95% noncondensing
Environment	Indoor

Terminals

	Loop +ve in/out
	Loop -ve in/out
	Cable screen continuity
	24 VDC +ve external supply
	24 VDC -ve external supply



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 12 June 2023 - 15:39